

Express Mail Certificate No. EV298592566US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR LETTERS PATENT

Applicants: LUNG-PO TSAI

Title : ELECTRICAL AIR BLOWER

5 Claims

3 Sheets of Drawings

William E. Pelton
Reg. No. 25,702
Donald S. Dowden
Reg. No. 20,701
Cooper & Dunham LLP
1185 Avenue of the Americas
New York, New York 10036
(212) 278-0400

ELECTRICAL AIR BLOWER

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an electrical air blower, and more particularly to an electrical air blower for pumping up an inflatable toy or doll.

2. Description of Related Art

Inflatable toys or dolls are generally pumped up by an inflator or a pump. The inflated toys should be detached from the inflator or pump and are used individually. However, air will gradually leak out from the inflated toys and thus they shrink, thereby needing to be pumped up again. Thus, the prior art inflators are very inconvenient for a user.

Therefore, the invention provides an electric air blower to mitigate or obviate the aforementioned problems.

SUMMARY OF THE INVENTION

The main objective of the present invention is to provide an electrical air blower which can continuously blow air into an inflatable toy.

Other objectives, advantages and novel features of the invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of an electric air blower in accordance with the invention;

Fig. 2 is an exploded perspective view of the electric air blower of Fig. 1; and

Fig. 3 is an operationally schematic view of the electric air blower used with an inflatable toy.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference to Figs. 1-2, an electric air blower (10) in accordance with the present invention has a cylindrical housing being composed of a first semi-housing (20) and a second semi-housing (30) attached to the first semi-housing (20) by fasteners (not numbered). The first semi-housing (20) and the second semi-housing (30) are symmetrical to each other.

The first semi-housing (20) has multiple first feet (21) formed at a lower side thereof and multiple first notches (22) respectively defined between the first feet (21). The second semi-housing (30) has multiple second feet (31) formed at a lower side thereof and multiple second notches (32).

With reference to Figs. 1-3, the first semi-housing (20) has multiple first air inlets (23) defined at a bottom plate (not numbered) thereof, and the second semi-housing (30) has multiple second air inlets (33) defined at a bottom plate (not numbered) thereof.

A first middle plate (24) is formed at a middle portion of the first semi-housing (20), and a first upper plate (25) is formed at an upper portion of the first semi-housing (20). A second middle plate (34) is formed at a middle portion of the second semi-housing (30), and a second upper plate (35) is formed at an upper portion of the second semi-housing (30).

A first bulb cap (26) is formed at a top surface of the first semi-housing (20), and a second bulb cap (36) is defined at a top surface of the second semi-housing (30) and matches the first bulb cap (26) to form a bulb chamber

1 (not numbered) for installing a bulb (70) therein. The first bulb cap (26) has
2 multiple first elongated slots (27) defined therethrough, and the second bulb cap
3 (36) has multiple second elongated slots (37) defined therethrough.

4 A first semi-groove (28) is transversally defined at an outer periphery of
5 the first semi-housing (20), and a second semi-groove (38) is defined at an outer
6 periphery of the second semi-housing (30) and matches the first semi-groove
7 (28). Multiple first air outlets (29) are defined through the top surface of the first
8 semi-housing (20), and multiple second air outlets (39) are defined through the
9 top surface of the second semi-housing (30).

10 An air impeller (40) is mounted between the bottom plates of the
11 semi-housings (20, 30) and the middle plates (24, 34). A motor (50) is mounted
12 between the upper plates (25, 35) and the middle plates (24, 34), and has an
13 output axle (51) extending downwards to drive the air impeller (40).

14 A circuit board (60) is installed in the first semi-housing (20) and
15 electrically connected with the motor (50). The bulb (70) is installed in the bulb
16 chambers being composed of the first bulb cap (26) and the second bulb cap (36).
17 When the bulb (70) is turned on, light can pass through the elongated slots (29,
18 39).

19 In use, an inflatable toy (80) with an opening (81) at a bottom thereof is
20 provided outside the air blower (10). The bottom of the inflatable toy (80) is
21 fastened by a cord (not shown) in the grooves (28, 38). Then, when the air
22 blower (10) is actuated, the air impeller (40) is driven by the motor (50) to rotate,
23 and air flows through the air inlets (23, 33) into the air blower (10) and is blown
24 out through the air outlets (29, 39) to inflate the inflatable toy (80). Thus, the

1 inflatable toy (80) can be continuously inflated to float in air as long as the
2 electric air blower (10) is actuated, and can be used as an advertising mark to
3 attract passers-by.

4 Moreover, the bulb (70) can be turned on to use the inflatable toy (80) at
5 night.

6 It is to be understood, however, that even though numerous
7 characteristics and advantages of the present invention have been set forth in the
8 foregoing description, together with details of the structure and function of the
9 invention, the disclosure is illustrative only, and changes may be made in detail,
10 especially in matters of shape, size, and arrangement of parts within the
11 principles of the invention to the full extent indicated by the broad general
12 meaning of the terms in which the appended claims are expressed.